

VIDEO SIGNAL PROCESSING UNIT, VIDEO SIGNAL PROCESSING METHOD AND RECORDING MEDIUM

Publication number: JP10004562 (A)

Publication date: 1998-01-06

Inventor(s): KORI TERUHIKO +

Applicant(s): SONY CORP +

Classification:

- international: **H04N5/91; H04N5/913; H04N9/79; H04N5/91; H04N5/913; H04N9/79; (IPC1-7): H04N5/91; H04N9/79**

- European: H04N5/913

Application number: JP19960150129 19960522

Priority number(s): JP19960150129 19960522; JP19960120887 19960418

Also published as:

JP3694981 (B2)

EP0802676 (A2)

EP0802676 (A3)


EP0802676 (B1)

US5883959 (A)

more >>

Abstract of **JP 10004562 (A)**

PROBLEM TO BE SOLVED: To ensure copying prevention effect while giving less disturbance onto a display on a television monitor. SOLUTION: Regular burst signals of (n+0)th to (n+3)th lines are replaced with burst signals a, b, c, d being copy prevention signals. For example, the signal (a) is obtained based on vector decomposition of the regular burst signal (n+0), and a mean value of phase vectors of the signals a, b, c, d is equal to a mean value of phase vectors of the regular burst signals of (n+0)th to (n+3)th lines. The signal (c) has a phase difference of 135 deg. with respect to the original regular burst signal (n+2), and then image is disturbed at reproduction by a VCR and a copy prevention effect is obtained. Furthermore, the signals a, b, d have a small phase difference of 45 deg. with respect to the original regular burst signals, a disturbance onto the monitor is small. Excess correction of image disturbance is reduced without adjustment of a plurality of AGC circuits with different characteristics.



Data supplied from the **espacenet** database — Worldwide